

WHAT IS CLAIMED IS:

1. A metal comprising:
a substrate with an exterior surface; and
5 a protective biofilm positioned on said exterior surface that reduces corrosion of said exterior surface;
wherein said metal is not steel, copper or aluminum.
2. The metal of Claim 1, wherein said metal is brass UNS-C26000.
10
3. The metal of Claim 1, wherein said biofilm is a bacterium.
4. The metal of Claim 3, wherein said bacterium is an aerobe.
- 15 5. The metal of Claim 4, wherein said bacterium is *Bacillus subtilis* or *Bacillus licheniformis*.
6. The metal of Claim 1, wherein said biofilm is between about 10 µm and about 20 µm thick.
20
7. A method for reducing metal corrosion comprising:
providing a metal with an exterior surface;
applying on said exterior surface a protective biofilm that reduces corrosion of said exterior surface;
25 wherein said metal is not copper, aluminum or steel.
8. The method of Claim 7, wherein said providing step includes the step of providing a metal that is brass UNS-C26000.
- 30 9. The method of Claim 7, wherein said applying step includes the step of applying a protective biofilm that is a bacterium.

10002317-105207

- TUESDAY, JULY 2000
10. The method of Claim 9, wherein said applying step includes the step of applying a bacterium that is an aerobe.
 11. The method of Claim 10, wherein said applying step includes the step of applying a bacterium that is *Bacillus subtilis* or *Bacillus licheniformis*.
 12. The method of Claim 7, wherein said applying step includes the step of applying a protective biofilm that is between about 10 µm and about 20 µm thick.
 - 10 13. The method of Claim 7, wherein said providing step includes the step of providing a metal that is immersed in a liquid.
 14. The method of Claim 13, wherein said providing step includes the step of providing a metal that is immersed in artificial seawater or Luria-Bertani medium.
 - 15 15. A metal comprising:
a substrate with an exterior surface; and
a protective biofilm positioned on said exterior surface that reduces corrosion of said exterior surface;
 - 20 wherein said protective biofilm is a bacterium that secretes a polyanionic chemical composition.
 16. The metal of Claim 15, wherein said metal is selected from the group consisting of aluminum, aluminum alloy, copper, a copper alloy, titanium, a titanium alloy, nickel and a nickel alloy.
 - 25 17. The metal of Claim 15, wherein said metal is steel.
 18. The metal of Claim 17, wherein said steel is mild steel-1010.
 - 30 19. The metal of Claim 15, wherein said bacterium is an aerobe.

- 1052017TE0000
20. The metal of Claim 19, wherein said bacterium is *E. coli*.
21. The metal of Claim 15, wherein said bacterium has been genetically engineered to secrete the polyanionic chemical composition.
- 5
22. The metal of Claim 15, wherein said polyanionic chemical composition is polyphosphate.
- 10
23. The metal of Claim 15, wherein said biofilm is between about 10 µm and about 20 µm thick.
24. A method for reducing corrosion comprising:
providing a metal with an exterior surface;
applying on said exterior surface a protective biofilm that reduces corrosion of
15 said exterior surface;
wherein said protective biofilm is a bacterium that secretes a polyanionic chemical composition.
25. The method of Claim 24, wherein said providing step includes the step of
20 providing a metal that is selected from the group consisting of aluminum, a aluminum alloy, copper, copper alloy, titanium, a titanium alloy, nickel and a nickel alloy.
26. The method of Claim 24, wherein said providing step includes the step of providing a metal that is steel.
- 25
27. The method of Claim 26, wherein said providing step includes the step of providing a metal that is mild steel-1010.
28. The method of Claim 24, wherein said applying step includes the step of
30 applying a bacterium that is an aerobe.

29. The method of Claim 28, wherein said applying step includes the step of applying a bacterium that is *E. coli*.
30. The method of Claim 24, wherein said applying step includes the step of applying a bacterium that has been genetically engineered to secrete the polyanionic chemical composition.
31. The method of Claim 24, wherein said applying step includes the step of applying a polyanionic chemical composition that is polyphosphate.
- 10 32. The method of Claim 24, wherein said applying step includes the step of applying a biofilm that is between about 10 µm and about 20 µm thick.
- 15 33. The method of Claim 24, wherein said providing step includes the step of providing a metal that is immersed in a liquid.
34. The method of Claim 24, wherein said providing step includes the step of providing a metal that is immersed in artificial seawater or Luria-Bertani medium.

10002317 - 102504